

## HOSE WHIP RESTRAINT

Perhaps the simplest and least expensive safety measure to implement, hose whip restraints prevent injury by restraining the hose in the event of an end fitting failure.

A hose whip restraint can be attached at any point where two hoses are joined, or to a pump's fluid end at the discharge side, or where a hose attaches to any piece of water jetting equipment.

**NOTE: Proper installation is essential. Never exceed safe working load. Follow manufacturer's recommendations and ratings.**



### STEEL WHIP RESTRAINT

Manufactured from stainless high tensile wire rope with spring-loaded retainers for easy installation and removal.

**21" (533 MM) • PART NO. ACWC SS-21**



**STEEL WHIP RESTRAINT**

### NYLON HOSE WHIP RESTRAINT

Made from durable strap with extra-heavy stitching. Fits any high pressure hose.

**31" (787 MM) • PART NO. ACWC NY-31**

**44" (1118 MM) • PART NO. ACWC NY-44**



**NYLON HOSE WHIP RESTRAINT**

## LUBRICANTS

MSDS sheets are available for all lubricants.

| LUBRICANT         | PART NUMBER | QTY    | DESCRIPTION                  |
|-------------------|-------------|--------|------------------------------|
| VISCOUS FLUID     | BJ 048-X*   | 6 oz.  | Synthetic Silicone Lubricant |
| AIR MOTOR OIL     | GP 041      | 32 oz. | Almo 525/ISO 46/SAE 10       |
| AUTO TRANS. FLUID | GP 042      | 32 oz. | Mercon®/Dexron® ATF          |
| ANTI-SEIZE        | GP 043      | 2 oz.  | Blue Goop®                   |
| MOTOR OIL         | GP 044      | 32 oz. | 10W-40                       |
| GEARBOX LUBE      | GP 046      | 32 oz. | 80W-85W-90                   |
| THREAD SEALANT    | GP 047      | 4 oz.  | ThreadMate®                  |
| GREASE            | GP 048      | 14 oz. | Synthetic Grease SHC 100     |



\* Please specify "fast" or "slow" for the type of viscous fluid needed.